

च.नं. :- ४९५

किस्पाङ्ग गाउँपालिका **गाउँ कार्यपालिकाको कार्यालय**

काहुले , तुवाकोट भागपालिक के र काहले , इवाकि भागमता प्रशास

ंबागमती प्रदेश, नेपाल

मिति: २०७९/०७/१६

विषय:- दररेट पेश गर्ने सम्बन्धमा ।

श्री आपूर्तिकर्ता, कम्पनी, फर्महरु (सवै),

प्रस्तुत विषयमा आ.व.०७९/०८० को लागि यस कार्यालयलाई संलग्न विवरण अनुसारको १ थान ILR फ्रिज खरिद गर्नु पर्ने भएकोले इच्छुक आपूर्तिकर्ता, कम्पनी, फर्महरुले यो सूचना प्रकाशित भएको मितिले ७ (सात) दिन भित्र ब्यवसाय दर्ता, भ्याट, प्यान दर्ताको प्रमाणपत्र, नवीकरण भएको इजाजत पत्रहरु र आ.ब.०७८/०७९ को करचुक्ता प्रमाण पत्रको प्रतिलिपी सहित संलग्न स्पेशिफिकेसन अनुसारको सामानको दररेट पेश गर्नु हुन यो सूचना प्रकाशित गरिएको छ ।

तपसिल:

सि.न.	सामानको विवरण	बजेट सिमा	कैपियत
٩	Ice Lined Refrigerator (ILR) (Specification by	४,००,०००।(चार लाख)	
	Family Welfare Division)	,	

महा प्रसादि दंगाल

(प्रमुख प्रशासकीय अधिकृत)



किस्पाङ गाउँपालिका गाउँ कार्यपालिकाको कार्यालय

anger, garanz

बागमती प्रदेश, नेपाल

Specification By Family Welfare Division Ice Lined Refrigerator (ILR)

S.N.	Specification	Bidders Remarks
	Manufacturers	
	Brand	
	Type/ Model	
	Country of origin	
1	Description of function	
1.1	Ice lined ref rigerators are used to store temperature sensitive vaccines/medicines.	
2	Operational requirements	
2.1	Only one vaccine storage compartment	
2.2	To maintain the temperatures of +2 °C to 8°C on minimum 8 hours electricity per day	<i>D</i> .
3	System Configuration	
3.1	Single compartment with voltage stabilizer as specified in 6.3	
4	Technical Specification	
4.1	Net storage capacity, minimum 50 liters with shelves/basket in place	
4.3	 Construction: Corrosion resistance: internal and external cabinet, lid and frame protected against corrosion. Bidders to specif y the materials used f or construction of internal and external cabinet. CFC free insulation Door with lock and handle Integrated digital temperatures display LCD/LED-01 (For displaying temperature inside the system and shall operate either f rom electrically or solar power). Refrigerant: The ref rigerator shall utilize CFC (Chlorof luorocarbon) f ree Hold over time: The ref rigerator shall maintain +2°C to +8°C f or minimum 48 hours during 	
4.6	power cuts at the ambient temperature +43°C Compressor: • Sealed heavy duty type	
4.7	Starts and operates on electricity supply from 220 to 260 volts. Control Panels: The thermostat thermometer and other visual displays like on of f switch. Power indicator must be positioned.	
4.8	Temperature Record History: Data loggers records minimum 30 days' temperature reading.	
5	Accessories, spares and consumables:	
5.1	Start Relay-1 Electronic Control Card / Thermostat - 1	P _d



	Capacitor - 1	3.50
	• Fuse - 1	
6	Operating environment	
6.1	The product of fered shall be designed to be stored and to operate normally under Nepal power supply, climate, temperature (+5°C to +45° C), low and high humidity conditions.	12
6.2	Unit power supply 220-240V Ac, 50 Hz f itted with appropriate plug. The power cable must be minimum 3 meters long.	Ye
6.3	Voltage stabilizer: Voltage stabilizer unit to fit the refrigerator shall be included, stabilizer to have the capacity of minimum 1KVA, normally operating input voltage of 110-270 V.	
7	Standard and safety requirements	15
7.1	WHO PQS E003 Certified product.	
8	User training	
8.1	Must be provided on site user training including how to use and maintain the equipment.	
9	Warranty	
9.1	Comprehensive warranty f or 2 years af ter installation.	
10	Maintenance service during warranty period	
10.1	During the warranty period supplier must ensure corrective/breakdown maintenance whenever required	10
11	Documentation	K Herrie
11.1	User manual in English	
11.2	Service (Technical /Maintenance) manual in English	

acupund

महा प्रसाद हंगाल प्रमुख प्रशासकीय अधिकृत